

Bore Size: 179.4 mm (7 1/16")

Model	Part Number (P/N)	Bore Size (mm / in)	Rated Working Pressure (MPa / psi)	Operating Chamber Rated Working Pressure (MPa / psi)	Recommended Operating Chamber Working Pressure (MPa / psi)	Oil volume for opening one set of ram assembly (L / gal)	Oil volume for closing one set of ram assembly (L / gal)	Locking Type	Closing Ratio λ	Specification of Rams Available	Top Connection	Bottom Connection	Overall Dimension			Approx Weight (kg / lb)
													L (mm / in)	W (mm / in)	H (mm / in)	
RS-C 7 1/16"-3,000psi Single Ram BOP	F9404	179.4 / 7 1/16	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1	Maximum Size of Pipe Ram 4 1/2"	Studded	Flanged	1520 / 59.84	540 / 21.26	450 / 17.72	900 / 1984
		179.4 / 7 1/16	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Studded	Studded	1520 / 59.84	540 / 21.26	280 / 11.02	830 / 1830
		179.4 / 7 1/16	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Flanged	Flanged	1520 / 59.84	540 / 21.26	629 / 24.76	970 / 2138
RS-C 7 1/16"-3,000psi Double Ram BOP	F9406	179.4 / 7 1/16	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1	Maximum Size of Pipe Ram 4 1/2"	Studded	Flanged	1520 / 59.84	540 / 21.26	715 / 28.15	1730 / 3814
		179.4 / 7 1/16	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Studded	Studded	1520 / 59.84	540 / 21.26	566 / 22.28	1660 / 3660
		179.4 / 7 1/16	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Flanged	Flanged	1520 / 59.84	540 / 21.26	864 / 34.02	1800 / 3968
RS-C 7 1/16"-3,000psi Single Ram BOP	RS11170	179.4 / 7 1/16	21 / 3000							Maximum Size of Pipe Ram 4 1/2"	Studded	Flanged	1190 / 46.85	380 / 14.96	335 / 13.19	350 / 772
		179.4 / 7 1/16	21 / 3000								Studded	Studded	1190 / 46.85	380 / 14.96	230 / 9.06	344 / 758
		179.4 / 7 1/16	21 / 3000								Flanged	Flanged	1190 / 46.85	380 / 14.96	450 / 17.72	365 / 805
RS-C 7 1/16"-3,000psi Double Ram BOP	RS11808	179.4 / 7 1/16	21 / 3000							Maximum Size of Pipe Ram 4 1/2"	Studded	Flanged	1190 / 46.85	380 / 14.96	550 / 21.65	550 / 1213
		179.4 / 7 1/16	21 / 3000								Studded	Studded	1190 / 46.85	380 / 14.96	458 / 18.03	540 / 1190
		179.4 / 7 1/16	21 / 3000								Flanged	Flanged	1190 / 46.85	380 / 14.96	642 / 25.28	570 / 1257
RS-C 7 1/16"-5,000psi Single Ram BOP	RS11137	179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1	Maximum Size of Pipe Ram 4 1/2"	Studded	Flanged	1520 / 59.84	540 / 21.26	450 / 17.72	900 / 1984
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Studded	Studded	1520 / 59.84	540 / 21.26	280 / 11.02	830 / 1830
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Flanged	Studded	1520 / 59.84	540 / 21.26	450 / 17.72	900 / 1984
RS-C 7 1/16"-5,000psi Double Ram BOP	RS11138	179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1	Maximum Size of Pipe Ram 4 1/2"	Flanged	Flanged	1520 / 59.84	540 / 21.26	629 / 24.76	970 / 2138
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Studded	Flanged	1520 / 59.84	540 / 21.26	743 / 29.25	1730 / 3814
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	4 : 1		Studded	Studded	1520 / 59.84	540 / 21.26	566 / 22.28	1660 / 3660
RS-CS 7 1/16"-5,000psi Single Ram BOP	RS11832	179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	9.77 : 1	Maximum Size of Pipe Ram 4 1/2"	Flanged	Studded	2112 / 83.15	540 / 21.26	475 / 18.70	1065 / 2348
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	9.77 : 1		Studded	Studded	2112 / 83.15	540 / 21.26	300 / 11.81	995 / 2194
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	9.77 : 1		Flanged	Flanged	2112 / 83.15	540 / 21.26	650 / 25.59	1135 / 2502
RS-CS 7 1/16"-5,000psi Double Ram BOP	RS11842	179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	9.77 : 1	Maximum Size of Pipe Ram 4 1/2"	Flanged	Studded	2112 / 83.15	540 / 21.26	781 / 30.75	2140 / 4718
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	9.77 : 1		Studded	Studded	2112 / 83.15	540 / 21.26	606 / 23.86	2070 / 4564
		179.4 / 7 1/16	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	3.2 / 0.85	4 / 1.06	Manual	9.77 : 1		Flanged	Flanged	2112 / 83.15	540 / 21.26	956 / 37.64	2210 / 4872
RS-C 7 1/16"-10,000psi Single Ram BOP	RS11157	179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	5.5 / 1.45	5.5 / 1.45	Manual	2.9 : 1	Maximum Size of Pipe Ram 4 1/2"	Studded	Flanged	2054 / 80.87	480 / 18.90	575 / 22.64	1220 / 2690
		179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	5.5 / 1.45	5.5 / 1.45	Manual	2.9 : 1		Flanged	Flanged	2054 / 80.87	480 / 18.90	746 / 29.37	1480 / 3263
		179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	5.5 / 1.45	5.5 / 1.45	Manual	2.9 : 1		Studded	Studded	2054 / 80.87	480 / 18.90	762 / 30.00	746 / 1645
RS-C 7 1/16"-10,000psi Double Ram BOP	RS11158	179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	5.5 / 1.45	5.5 / 1.45	Manual	2.9 : 1	Maximum Size of Pipe Ram 4 1/2"	Studded	Flanged	2054 / 80.87	480 / 18.90	910 / 35.83	2240 / 4938
		179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	5.5 / 1.45	5.5 / 1.45	Manual	2.9 : 1		Flanged	Flanged	2054 / 80.87	480 / 18.90	1081 / 12.56	2488 / 5485
		179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	17.5 / 4.62	18.7 / 4.94	Manual	11.1 : 1		Studded	Flanged	1928 / 75.91	770 / 30.31	605 / 23.82	1823 / 4019
RS-CS 7 1/16"-10,000psi Single Ram BOP	RS11857	179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	17.5 / 4.62	18.7 / 4.94	Manual	11.1 : 1	Maximum Size of Pipe Ram 4 1/2"	Studded	Studded	1928 / 75.91	770 / 30.31	430 / 16.93	1671 / 3684
		179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	17.5 / 4.62	18.7 / 4.94	Manual	11.1 : 1		Flanged	Flanged	1928 / 75.91	770 / 30.31	780 / 30.71	1963 / 4328
		179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	17.5 / 4.62	18.7 / 4.94	Manual	11.1 : 1		Studded	Flanged	1928 / 75.91	770 / 30.31	1005 / 39.57	3626 / 7994
RS-CS 7 1/16"-10,000psi Double Ram BOP	RS11858	179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	17.5 / 4.62	18.7 / 4.94	Manual	11.1 : 1	Maximum Size of Pipe Ram 4 1/2"	Studded	Studded	1928 / 75.91	770 / 30.31	830 / 32.68	3500 / 7716
		179.4 / 7 1/16	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	17.5 / 4.62	18.7 / 4.94	Manual	11.1 : 1		Flanged	Flanged	1928 / 75.91	770 / 30.31	1180 / 46.46	3866 / 8523

Bore Size: 228.6 mm (9")

Model	Part Number (P/N)	Bore Size (mm / in)	Rated Working Pressure (MPa / psi)	Operating Chamber Rated Working Pressure (MPa / psi)	Recommended Operating Chamber Working Pressure (MPa / psi)	Oil volume for opening one set of ram assembly (L / gal)	Oil volume for closing one set of ram assembly (L / gal)	Locking Type	Body Side Outlet (in-psi)	Closing Ratio λ	Specification of Rams Available	Top Connection	Bottom Connection	Overall Dimension			Approx Weight (kg / lb)
														L (mm / in)	W (mm / in)	H (mm / in)	
RS-C 9"-3,000psi Single Ram BOP	RS11144	228.6 / 9	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	4 / 1.06	4.8 / 1.27	Manual		4 : 1		Studded	Flanged	1726 / 67.95	595 / 23.43 *	430 / 16.93	875 / 1929
		228.6 / 9	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	4 / 1.06	4.8 / 1.27	Manual		4 : 1		Studded	Studded	1726 / 67.95	595 / 23.43 *	280 / 11.02	820 / 1808
		228.6 / 9	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	4 / 1.06	4.8 / 1.27	Manual		4 : 1	Maximum Size	Flanged	Flanged	1726 / 67.95	595 / 23.43 *	580 / 22.83	930 / 2050
RS-C 9"-3,000psi Double Ram BOP	RS11165	228.6 / 9	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	4 / 1.06	4.8 / 1.27	Manual	3 1/8-3,000 *	4 : 1	of Pipe Ram 5 1/2"	Studded	Flanged	1726 / 67.95	595 / 23.43 *	710 / 27.95	1695 / 3737
		228.6 / 9	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	4 / 1.06	4.8 / 1.27	Manual	3 1/8-3,000 *	4 : 1		Studded	Studded	1726 / 67.95	595 / 23.43 *	560 / 22.25	1640 / 3616
		228.6 / 9	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	4 / 1.06	4.8 / 1.27	Manual	3 1/8-3,000 *	4 : 1		Flanged	Flanged	1726 / 67.95	595 / 23.43 *	860 / 33.86	1750 / 3858
RS-C 9"-3,000psi Single Ram BOP	RS11893	228.6 / 9	21 / 3000								Maximum Size of Pipe Ram 5 1/2"	Studded	Studded	1461 / 57.52	585 / 23.31	280 / 11.02	382 / 842
RS-C 9"-5,000psi Single Ram BOP	RS11163	228.6 / 9	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	12 / 3.17	13.2 / 3.49	Manual	3 1/8-5,000 *	7.7 : 1		Studded	Flanged	2032 / 80.00	865 / 34.06 *	620 / 24.41	2100 / 4630
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	12 / 3.17	13.2 / 3.49	Manual	3 1/8-5,000 *	7.7 : 1		Studded	Studded	2032 / 80.00	865 / 34.06 *	425 / 16.73	1990 / 4387
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	12 / 3.17	13.2 / 3.49	Manual	3 1/8-5,000 *	7.7 : 1	Maximum Size	Flanged	Flanged	2032 / 80.00	865 / 34.06 *	820 / 32.28	2210 / 4872
RS-C 9"-5,000psi Double Ram BOP	RS11160	228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	12 / 3.17	13.2 / 3.49	Manual	3 1/8-5,000 *	7.7 : 1	of Pipe Ram 7"	Studded	Flanged	2032 / 80.00	865 / 34.06 *	1025 / 40.35	4090 / 9017
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	12 / 3.17	13.2 / 3.49	Manual	3 1/8-5,000 *	7.7 : 1		Studded	Studded	2032 / 80.00	865 / 34.06 *	830 / 32.68	3980 / 8774
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	12 / 3.17	13.2 / 3.49	Manual	3 1/8-5,000 *	7.7 : 1		Flanged	Flanged	2032 / 80.00	865 / 34.06 *	1225 / 48.23	4200 / 9259
RS-CS 9"-5,000psi Single Ram BOP	RS11849	228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	18.4 / 4.86	19.8 / 5.23	Manual	3 1/8-5,000 *	11.1 : 1		Studded	Flanged	2074 / 81.65	865 / 34.06 *	620 / 24.41	2260 / 4982
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	18.4 / 4.86	19.8 / 5.23	Manual	3 1/8-5,000 *	11.1 : 1		Studded	Studded	2074 / 81.65	865 / 34.06 *	425 / 16.73	2150 / 4740
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	18.4 / 4.86	19.8 / 5.23	Manual	3 1/8-5,000 *	11.1 : 1	Maximum Size	Flanged	Flanged	2074 / 81.65	865 / 34.06 *	820 / 32.28	2370 / 5225
RS-CS 9"-5,000psi Double Ram BOP	RS11850	228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	18.4 / 4.86	19.8 / 5.23	Manual	3 1/8-5,000 *	11.1 : 1	of Pipe Ram 7"	Studded	Flanged	2074 / 81.65	865 / 34.06 *	1025 / 40.35	4394 / 9687
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	18.4 / 4.86	19.8 / 5.23	Manual	3 1/8-5,000 *	11.1 : 1		Studded	Studded	2074 / 81.65	865 / 34.06 *	830 / 32.68	4284 / 9445
		228.6 / 9	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	18.4 / 4.86	19.8 / 5.23	Manual	3 1/8-5,000 *	11.1 : 1		Flanged	Flanged	2074 / 81.65	865 / 34.06 *	1225 / 48.23	4504 / 9930
RS-C 9"-5,000psi Single Ram BOP	RS11877	228.6 / 9	35 / 5000								Maximum Size of Pipe Ram 7"	Flanged	Flanged	1624 / 63.94	733 / 28.86	815 / 32.09	2014 / 4440
RS-C 9"-10,000psi Single Ram BOP	RS11837	228.6 / 9	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	11.4 / 3.01	12.6 / 3.33	Manual	2 9/16-10,000 *	7.7 : 1		Studded	Studded	2046 / 80.55	915 / 36.02 *	505 / 19.88	2585 / 5699
		228.6 / 9	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	11.4 / 3.01	12.6 / 3.33	Manual	2 9/16-10,000 *	7.7 : 1		Studded	Flanged	2046 / 80.55	915 / 36.02 *	715 / 28.15	2805 / 6184
		228.6 / 9	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	11.4 / 3.01	12.6 / 3.33	Manual	2 9/16-10,000 *	7.7 : 1	Maximum Size	Flanged	Flanged	2046 / 80.55	915 / 36.02 *	925 / 36.12	3025 / 6669
RS-C 9"-10,000psi Double Ram BOP	RS11838	228.6 / 9	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	11.4 / 3.01	12.6 / 3.33	Manual	2 9/16-10,000 *	7.7 : 1	of Pipe Ram 7"	Studded	Studded	2046 / 80.55	915 / 36.02 *	920 / 36.22	5260 / 11596
		228.6 / 9	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	11.4 / 3.01	12.6 / 3.33	Manual	2 9/16-10,000 *	7.7 : 1		Studded	Flanged	2046 / 80.55	915 / 36.02 *	1130 / 44.49	5480 / 12081
		228.6 / 9	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	11.4 / 3.01	12.6 / 3.33	Manual	2 9/16-10,000 *	7.7 : 1		Flanged	Flanged	2046 / 80.55	915 / 36.02 *	1345 / 52.95	5700 / 12566

Bore Size: 279.4 mm (11")

Model	Part Number (P/N)	Bore Size (mm / in)	Rated Working Pressure (MPa / psi)	Operating Chamber Rated Working Pressure (MPa / psi)	Recommended Operating Chamber Working Pressure (MPa / psi)	Oil volume for opening one set of ram assembly (L / gal)	Oil volume for closing one set of ram assembly (L / gal)	Locking Type	Body Side Outlet (in-psi)	Closing Ratio λ	Specification of Rams Available	Top Connection	Bottom Connection	Overall Dimension			Approx Weight (kg / lb)
														L (mm / in)	W (mm / in)	H (mm / in)	
RS-C 11"-3,000psi Single Ram	RS11161	279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	10.6 / 2.80	12 / 3.17	Manual		6 : 1		Studded	Flanged	2070 / 81.50	755 / 29.72 *	574 / 22.60	1735 / 3825 (2050 / 4519)
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	10.6 / 2.80	12 / 3.17	Manual		6 : 1		Studded	Studded	(2448 / 96.38)	755 / 29.72 *	460 / 15.98	1630 / 3594 (1945 / 4288)
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	10.6 / 2.80	12 / 3.17	Manual		6 : 1	Maximum Size	Flanged	Flanged		755 / 29.72 *	690 / 27.17	1840 / 4057 (2155 / 4751)
RS-C 11"-3,000psi Double Ram BOP	RS11162	279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	10.6 / 2.80	12 / 3.17	Manual	3 1/8-3,000 *	6 : 1	of Pipe Ram 7"	Studded	Flanged	2070 / 81.50	755 / 29.72 *	957 / 37.68	3655 / 8058 (3950 / 8708)
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	10.6 / 2.80	12 / 3.17	Manual	3 1/8-3,000 *	6 : 1		Studded	Studded	(2448 / 96.38)	755 / 29.72 *	800 / 31.50	3550 / 7826 (3865 / 8521)
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	10.6 / 2.80	12 / 3.17	Manual	3 1/8-3,000 *	6 : 1		Flanged	Flanged		755 / 29.72 *	1120 / 44.09	3760 / 8289 (4075 / 8984)
RS-CS 11"-3,000psi Single Ram BOP	RS11920	279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-3,000 *	11.1 : 1		Studded	Flanged	2144 / 84.41	725 / 28.54 *	574 / 22.60	2088 / 4603
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-3,000 *	11.1 : 1	Maximum Size	Flanged	Flanged	2144 / 84.41	725 / 28.54 *	742 / 29.21	2310 / 5093
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-3,000 *	11.1 : 1	of Pipe Ram 7"	Studded	Studded	2144 / 84.41	725 / 28.54 *	789 / 31.06	4030 / 8885
RS-CS 11"-3,000psi Double Ram BOP	RS11921	279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-3,000 *	11.1 : 1		Studded	Flanged	2144 / 84.41	725 / 28.54 *	957 / 37.68	4245 / 9359
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-3,000 *	11.1 : 1		Flanged	Flanged	2144 / 84.41	725 / 28.54 *	1125 / 44.29	4465 / 9844
		279.4 / 11	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-3,000 *	11.1 : 1		Studded	Studded	2144 / 84.41	725 / 28.54 *	789 / 31.06	4030 / 8885
RS-C 11"-5,000psi Single Ram BOP	RS11153	279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	10.3 / 2.72	11.8 / 3.12	Manual	3 1/8-5,000 *	5.98 : 1		Studded	Flanged	2120 / 83.46	865 / 34.06 *	670 / 26.38	2260 / 4982
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	10.3 / 2.72	11.8 / 3.12	Manual	3 1/8-5,000 *	5.98 : 1	Maximum Size	Flanged	Flanged	2120 / 83.46	865 / 34.06 *	900 / 35.43	2487 / 5483
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	10.3 / 2.72	11.8 / 3.12	Manual	3 1/8-5,000 *	5.98 : 1	of Pipe Ram 7 5/8"	Studded	Studded	2120 / 83.46	865 / 34.06 *	1065 / 44.93	4035 / 8896
RS-C 11"-5,000psi Double Ram BOP	F9403	279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	10.3 / 2.72	11.8 / 3.12	Manual	3 1/8-5,000 *	5.98 : 1		Studded	Flanged	2120 / 83.46	865 / 34.06 *	830 / 32.68	4262 / 9396
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	10.3 / 2.72	11.8 / 3.12	Manual	3 1/8-5,000 *	5.98 : 1		Flanged	Flanged	2120 / 83.46	865 / 34.06 *	1300 / 51.18	4490 / 9899
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	10.3 / 2.72	11.8 / 3.12	Manual	3 1/8-5,000 *	5.98 : 1		Studded	Flanged	2232 / 87.87	865 / 34.06 *	670 / 26.38	2619 / 5774
RS-CS 11"-5,000psi Single Ram BOP	RS11963	279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-5,000 *	11.1 : 1		Studded	Flanged	2232 / 87.87	865 / 34.06 *	900 / 35.43	2856 / 6296
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-5,000 *	11.1 : 1	Maximum Size	Flanged	Flanged	2232 / 87.87	865 / 34.06 *	900 / 35.43	2856 / 6296
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-5,000 *	11.1 : 1	of Pipe Ram 7 5/8"	Studded	Studded	2232 / 87.87	865 / 34.06 *	830 / 32.68	4766 / 10507
RS-CS 11"-5,000psi Double Ram BOP	RS11863	279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-5,000 *	11.1 : 1		Studded	Flanged	2232 / 87.87	865 / 34.06 *	1065 / 44.93	5003 / 11030
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-5,000 *	11.1 : 1		Flanged	Flanged	2232 / 87.87	865 / 34.06 *	1305 / 51.38	5240 / 11552
		279.4 / 11	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	22 / 5.81	24 / 6.34	Manual	3 1/8-5,000 *	11.1 : 1		Studded	Flanged	2250 / 88.58	1020 / 40.16 *	803 / 31.61	4130 / 9105
RS-C 11"-10,000psi Single Ram BOP	RS11133	279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	13 / 3.43	14.7 / 3.88	Manual	3 1/16-10,000 *	7.72 : 1		Studded	Flanged	2250 / 88.58	1020 / 40.16 *	1040 / 40.94	4415 / 9733
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	13 / 3.43	14.7 / 3.88	Manual	3 1/16-10,000 *	7.72 : 1	Maximum Size	Flanged	Flanged	2250 / 88.58	1020 / 40.16 *	1040 / 40.94	4415 / 9733
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	13 / 3.43	14.7 / 3.88	Manual	3 1/16-10,000 *	7.72 : 1	of Pipe Ram 7 5/8"	Studded	Flanged	2250 / 88.58	1020 / 40.16 *	1233 / 48.54	7460 / 16446
RS-C 11"-10,000psi Double Ram BOP	RS11134	279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	13 / 3.43	14.7 / 3.88	Manual	3 1/16-10,000 *	7.72 : 1		Studded	Flanged	2250 / 88.58	1020 / 40.16 *	1470 / 57.87	7730 / 17042
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	13 / 3.43	14.7 / 3.88	Manual	3 1/16-10,000 *	7.72 : 1		Flanged	Flanged	2250 / 88.58	1020 / 40.16 *	1470 / 57.87	7730 / 17042
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	30 / 7.93	33 / 8.72	Manual	3 1/16-10,000 *	9.55 : 1		Studded	Flanged	2445 / 96.26	920 / 36.22 *	803 / 31.61	4160 / 9171
RS-CS 11"-10,000psi Single Ram BOP	RS11821	279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	30 / 7.93	33 / 8.72	Manual	3 1/16-10,000 *	9.55 : 1		Studded	Flanged	2445 / 96.26	920 / 36.22 *	1040 / 40.94	4445 / 9800
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	30 / 7.93	33 / 8.72	Manual	3 1/16-10,000 *	9.55 : 1	Maximum Size	Flanged	Flanged	2445 / 96.26	920 / 36.22 *	1040 / 40.94	4445 / 9800
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	30 / 7.93	33 / 8.72	Manual	3 1/16-10,000 *	9.55 : 1	of Pipe Ram 7 5/8"	Studded	Flanged	2445 / 96.26	920 / 36.22 *	1233 / 48.54	7500 / 16535
RS-CS 11"-10,000psi Double Ram BOP	RS11174	279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	30 / 7.93	33 / 8.72	Manual	3 1/16-10,000 *	9.55 : 1		Studded	Flanged	2445 / 96.26	920 / 36.22 *	1470 / 57.87	7790 / 17174
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	30 / 7.93	33 / 8.72	Manual	3 1/16-10,000 *	9.55 : 1		Flanged	Flanged	2445 / 96.26	920 / 36.22 *	1470 / 57.87	7790 / 17174
		279.4 / 11	70 / 10000	21 / 3000	8.4-10.5 / 1200-1500	30 / 7.93	33 / 8.72	Manual	3 1/16-10,000 *	9.55 : 1		Studded	Flanged	2445 / 96.26	920 / 36.22 *	1470 / 57.87	7790 / 17174

Bore Size: 425.5 mm (16 3/4"), 476.25 mm (18 3/4"), 527 mm (20 3/4")

Model	Part Number (P/N)	Bore Size (mm / in)	Rated Working Pressure (MPa / psi)	Operating Chamber Rated Working Pressure (MPa / psi)	Recommended Operating Chamber Working Pressure (MPa / psi)	Oil volume for opening one set of ram assembly (L / gal)	Oil volume for closing one set of ram assembly (L / gal)	Locking Type	Body Side Outlet (in-psi)	Closing Ratio λ	Specification of Rams Available	Top Connection	Bottom Connection	Overall Dimension			Approx Weight (kg / lb)
														L (mm / in)	W (mm / in)	H (mm / in)	
RS-C 16 3/4"-3,000psi Single Ram BOP	RS18010	425.5 / 16 3/4	21/ 3000	21 / 3000	8.4-10.5 / 1200-1500	44 / 11.62	51 / 13.47	Manual	4 1/16-3,000 ★	6.4 : 1	Maximum Size of Pipe Ram 13 3/8"	Studded	Flanged	3930 / 154.7	1100 / 43.3 ★	755 / 29.7	4895 / 10792
RS-C 16 3/4"-3,000psi Double Ram BOP	RS18011	425.5 / 16 3/4	21/ 3000	21 / 3000	8.4-10.5 / 1200-1500	44 / 11.62	51 / 13.47	Manual	4 1/16-3,000 ★	6.4 : 1		Studded	Flanged	3930 / 154.7	1100 / 43.3 ★	1265 / 49.8	9538 / 21028
RS-CS 16 3/4"-5,000psi Single Ram BOP	RS11175	425.5 / 16 3/4	35/ 5000	21 / 3000	8.4-10.5 / 1200-1500	44 / 11.62	51 / 13.47	Manual	3 1/8-5,000 ★	7.4 : 1	Maximum Size of Pipe Ram 13 3/8"	Flanged	Flanged	3098 / 121.97	1188 / 46.77 ★	1075 / 42.32	6860 / 15124
RS-CS 16 3/4"-5,000psi Double Ram BOP	RS11176	425.5 / 16 3/4	35/ 5000	21 / 3000	8.4-10.5 / 1200-1500	44 / 11.62	51 / 13.47	Manual	3 1/8-5,000 ★	7.4 : 1		Flanged	Flanged	3098 / 121.97	1188 / 46.77 ★	1585 / 62.40	12496 / 27549
RS-CS 18 3/4"-5,000psi Single Ram BOP	RS11843	476.25 / 8 3/4	35/ 5000	21 / 3000	8.4-10.5 / 1200-1500	53 / 14.00	62 / 16.38	Manual	4 1/16-5,000 ★	6.89 : 1	Maximum Size of Pipe Ram 13 3/8"	Flanged	Flanged	3416 / 134.49	1325 / 52.17 ★	1242 / 48.90	9370 / 20657
RS-CS 18 3/4"-5,000psi Double Ram BOP	RS11844	476.25 / 8 3/4	35/ 5000	21 / 3000	8.4-10.5 / 1200-1500	53 / 14.00	62 / 16.38	Manual	4 1/16-5,000 ★	6.89 : 1		Flanged	Flanged	3416 / 134.49	1325 / 52.17 ★	1797 / 70.75	16920 / 37302
RS-C 20 3/4"-3,000psi Single Ram BOP	RS11164	527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 ★	3.7 : 1	Maximum Size of Pipe Ram 16"	Studded	Studded	3206 / 126.22	1180 / 46.46 ★	590 / 23.23	4765 / 10505
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 ★	3.7 : 1		Studded	Flanged	3206 / 126.22	1180 / 46.46 ★	850 / 33.46	4995 / 11012
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 ★	3.7 : 1		Flanged	Flanged	3206 / 126.22	1180 / 46.46 ★	1100 / 43.31	5365 / 11828
RS-C 20 3/4"-3,000psi Double Ram BOP	RS11132	527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 ★	3.7 : 1	of Pipe Ram 16"	Studded	Flanged	3206 / 126.22	1180 / 46.46 ★	1280 / 50.39	9530 / 21010
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 ★	3.7 : 1		Studded	Studded	3206 / 126.22	1180 / 46.46 ★	1030 / 40.55	9160 / 20194
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 ★	3.7 : 1		Flanged	Flanged	3206 / 126.22	1180 / 46.46 ★	1540 / 60.63	9900 / 20040
RS-CS 20 3/4"-3,000psi Single Ram BOP	RS11896	527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-3,000 ★	9.55 : 1	Maximum Size of Pipe Ram 16"	Studded	Studded	3818 / 150.31	1180 / 46.46 ★	590 / 23.23	5678 / 12518
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-3,000 ★	9.55 : 1		Studded	Flanged	3818 / 150.31	1180 / 46.46 ★	850 / 33.46	5908 / 13025
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-3,000 ★	9.55 : 1		Flanged	Flanged	3818 / 150.31	1180 / 46.46 ★	1100 / 43.31	6278 / 13841
RS-CS 20 3/4"-3,000psi Double Ram BOP	RS11897	527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-3,000 ★	9.55 : 1	of Pipe Ram 16"	Studded	Flanged	3818 / 150.31	1180 / 46.46 ★	1280 / 50.39	10413 / 22957
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-3,000 ★	9.55 : 1		Studded	Studded	3818 / 150.31	1180 / 46.46 ★	1030 / 40.55	10413 / 22957
		527 / 20 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-3,000 ★	9.55 : 1		Flanged	Flanged	3818 / 150.31	1180 / 46.46 ★	1540 / 60.63	10783 / 23772

Bore Size: 539.8 mm (21 1/4"), 679.4 mm (26 3/4")

Model	Part Number (P/N)	Bore Size (mm / in)	Rated Working Pressure (MPa / psi)	Operating Chamber Rated Working Pressure (MPa / psi)	Recommended Operating Chamber Working Pressure (MPa / psi)	Oil volume for opening one set of ram assembly (L / gal)	Oil volume for closing one set of ram assembly (L / gal)	Locking Type	Body Side Outlet (in-psi)	Closing Ratio λ	Specification of Rams Available	Top Connection	Bottom Connection	Overall Dimension			Approx Weight (kg / lb)
														L (mm / in)	W (mm / in)	H (mm / in)	
RS-C 21 1/4"-2,000psi Single Ram BOP	RS11154	539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 *	5.2 : 1	Maximum Size of Pipe Ram 16"	Studded	Flanged	3206 / 126.22	1180 / 46.46 *	705 / 27.76	4725 / 10417
		539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 *	5.2 : 1		Flanged	Flanged	3206 / 126.22	1180 / 46.46 *	895 / 35.24	4965 / 10946
		539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 *	5.2 : 1		Studded	Studded	3206 / 126.22	1180 / 46.46 *	525 / 20.67	4525 / 9976
RS-C 21 1/4"-2,000psi Double Ram BOP	RS11139	539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 *	5.2 : 1	Maximum Size of Pipe Ram 16"	Studded	Flanged	3206 / 126.22	1180 / 46.46 *	1155 / 45.47	8980 / 19797
		539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 *	5.2 : 1		Studded	Studded	3206 / 126.22	1180 / 46.46 *	975 / 38.39	8780 / 19357
		539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	24 / 6.34	27 / 7.13	Manual	4 1/16-3,000 *	5.2 : 1		Flanged	Flanged	3206 / 126.22	1180 / 46.46 *	1345 / 52.95	9220 / 20327
RS-CS 21 1/4"-2,000psi Single Ram BOP	RS11190	539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-10,000 *	9.55 : 1	Maximum Size of Pipe Ram 16"	Studded	Flanged	3818 / 150.31	1180 / 46.46 *	705 / 27.76	5268 / 11614
		539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-10,000 *	9.55 : 1		Flanged	Flanged	3818 / 150.31	1180 / 46.46 *	895 / 35.24	5542 / 12218
RS-CS 21 1/4"-2,000psi Double Ram BOP	RS11898	539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-10,000 *	9.55 : 1	Maximum Size of Pipe Ram 16"	Studded	Flanged	3818 / 150.31	1180 / 46.46 *	1155 / 45.47	10116 / 22302
		539.8 / 21 1/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	48 / 12.68	54 / 14.27	Manual	4 1/16-10,000 *	9.55 : 1		Flanged	Flanged	3818 / 150.31	1180 / 46.46 *	1345 / 52.95	10390 / 22906
RS-CS 21 1/4"-5,000psi Single Ram BOP	RS11810	539.8 / 21 1/4	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	60 / 15.85	63 / 16.64	Manual	4 1/16-5,000 *	9.55 : 1	Maximum Size of Pipe Ram 16"	Studded	Studded	3494 / 137.56	1387 / 54.61 *	1445 / 56.89	16935 / 37335
		539.8 / 21 1/4	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	60 / 15.85	63 / 16.64	Manual	4 1/16-5,000 *	9.55 : 1		Studded	Flanged	3494 / 137.56	1387 / 54.61 *	1656 / 65.20	17625 / 49463
		539.8 / 21 1/4	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	60 / 15.85	63 / 16.64	Manual	4 1/16-5,000 *	9.55 : 1		Flanged	Flanged	3494 / 137.56	1387 / 54.61 *	1967 / 77.44	18315 / 40378
RS-CS 21 1/4"-5,000psi Double Ram BOP	RS11809	539.8 / 21 1/4	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	60 / 15.85	63 / 16.64	Manual	4 1/16-5,000 *	9.55 : 1	Maximum Size of Pipe Ram 16"	Studded	Studded	3494 / 137.56	1387 / 54.61 *	860 / 33.86	9140 / 20150
		539.8 / 21 1/4	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	60 / 15.85	63 / 16.64	Manual	4 1/16-5,000 *	9.55 : 1		Studded	Flanged	3494 / 137.56	1387 / 54.61 *	1170 / 46.06	9830 / 21671
		539.8 / 21 1/4	35 / 5000	21 / 3000	8.4-10.5 / 1200-1500	60 / 15.85	63 / 16.64	Manual	4 1/16-5,000 *	9.55 : 1		Flanged	Flanged	3494 / 137.56	1387 / 54.61 *	1382 / 54.41	10520 / 23193
RS-CS 26 3/4"-2,000psi Single Ram BOP	RS11880	679.4 / 26 3/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1	Maximum Size of Pipe Ram 20"	Flanged	Flanged	4206 / 165.59	1810 / 71.26 *	1180 / 46.46	10900 / 24030
		679.4 / 26 3/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Flanged	Studded	4206 / 165.59	1810 / 71.26 *	940 / 37.01	9980 / 22002
		679.4 / 26 3/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Studded	Studded	4206 / 165.59	1810 / 71.26 *	710 / 27.95	9050 / 19952
RS-CS 26 3/4"-2,000psi Double Ram BOP	RS11926	679.4 / 26 3/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1	Maximum Size of Pipe Ram 20"	Flanged	Flanged	4206 / 165.59	1810 / 71.26 *	1800 / 70.87	20120 / 44357
		679.4 / 26 3/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Flanged	Studded	4206 / 165.59	1810 / 71.26 *	1530 / 60.24	19210 / 42351
		679.4 / 26 3/4	14 / 2000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Studded	Studded	4206 / 165.59	1810 / 71.26 *	1340 / 52.76	18110 / 39926
RS-CS 26 3/4"-3,000psi Single Ram BOP	RS11822	679.4 / 26 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1	Maximum Size of Pipe Ram 20"	Flanged	Flanged	4206 / 165.59	1810 / 71.26 *	1250 / 49.21	11135 / 24548
		679.4 / 26 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Flanged	Studded	4206 / 165.59	1810 / 71.26 *	980 / 38.58	10177 / 22436
		679.4 / 26 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Studded	Studded	4206 / 165.59	1810 / 71.26 *	710 / 27.95	9210 / 20305
RS-CS 26 3/4"-3,000psi Double Ram BOP	RS11804	679.4 / 26 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1	Maximum Size of Pipe Ram 20"	Flanged	Flanged	4206 / 165.59	1810 / 71.26 *	1882 / 74.09	20280 / 44710
		679.4 / 26 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Flanged	Studded	4206 / 165.59	1810 / 71.26 *	1612 / 63.47	19325 / 42604
		679.4 / 26 3/4	21 / 3000	21 / 3000	8.4-10.5 / 1200-1500	67 / 17.70	70 / 18.49	Manual	4 1/16-3,000 *	12.645 : 1		Studded	Studded	4206 / 165.59	1810 / 71.26 *	1340 / 52.76	18310 / 40367